

## E series Specifications

Model	E3 series	E4 series	E5 series
Table size	40" x 16"	48.8" x 18"	60" x 20"
Table T-slot (W x N)	0.71"x4	0.71"x4	0.71"x5
Max. table load (Center)	990 lbs	1320 lbs	1760 lbs
X travel	33.9"	41.7"	52"
Y travel	20"	22"	26"
Z travel	24"	24"	27.6"
Spindle nose to table surface	4.8" ~28.8"	4.8" ~28.9"	4.3" ~31.8"
Spindle center to column	21.7"	23.6"	27.5"
Table surface to floor	32.5"	33.3"	32.5"
Spindle speed	<b>6,000 R.P.M. (8,000 R.P.M. is optional)</b>		
Spindle motor	10 HP	10 HP	15 HP
Spindle taper	CAT#40	CAT#40	CAT#40
Spindle belt	8YU belt	8YU belt	8YU belt
Ball-screw diameter	01.26"	01.26"	01.57"
Pitch of ball-screw	0.20"	0.20"	0.24"
X and Y axis rapid feed	320 ipm	320 ipm	320 ipm
Z axis rapid feed	320 ipm	320 ipm	320 ipm
Cutting feed	200 ipm	200 ipm	200 ipm
ATC type (OPI)	<b>Armless and Arm type are optional</b>		
ATC tool no.	16 tools	16 tools	20 tools
Max. tool diameter	03.54"	03.54"	03.54"
Max. tool weight	015.4 lbs	015.4 lbs	015.4 lbs
Positioning accuracy	±0.0004"	±0.0004"	±0.0004"
Repeatability accuracy	±0.0002"	±0.0002"	±0.0002"
Machine weight	6,820 lbs	9,460 lbs	12,320 lbs
Dimension A X - static	66"	82"	103"
Dimension B X- full travel	99"	124"	155"
Dimension C width	83"	87"	96"
Dimension D height	96"	97"	101"
<b>Unit Prices</b>	<b>\$48,675</b>	<b>\$54,750</b>	<b>\$59,750</b>